



PRODUCT-DETAILS

MLP125-C-A

SHRINK-KON 25X1,2M TRANSP.



General Information

Extended Product Type	MLP125-C-A
Product ID	7TCA017300R0430
EAN	5414363104896
Catalog Description	SHRINK-KON 25X1,2M TRANSP.
Long Description	Heat Shrink Tubing, Flexible for High Specifications, UL/CSA Listed, Thin Wall, Shrink Ratio 2:1, 1/8 Inch/3.2mm Expanded Diameter, Transparent, 25 X 1.22M Lengths

Ordering

EAN	5414363104896
-----	---------------

Dimensions

Product Net Weight	.016 lb 7.256 g
--------------------	--------------------

Container Information

Package Level 2 Units	25 piece
Package Level 2 Width	4.1 in 104 mm
Package Level 2 Height	4.2 in 107 mm

Package Level 2 Depth /
Length

49.3 in
1252 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Transparent
Flammability Hazard Rating	Flame Retardant
Number of Batteries	0
Process Temperature Rating	-67 to +212 °F -55 to +100 °C
Product Name	Plastic conduit
Product Type	Thin-Wall Heat Shrinkable Tubing
Shrink Ratio	2:1
Shrink Temperature	194 °F 90 °C
Thickness	Thin
UPC	786210597980

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	MLP125-C-A
Instructions and Manuals	MLP125-C-A

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

