



PRODUCT-DETAILS

MLP93-C-E

SHRINK-KON 150M TRANSPARENT



General Information

Extended Product Type	MLP93-C-E
Product ID	7TCA017300R0920
EAN	5415022276619
Catalog Description	SHRINK-KON 150M TRANSPARENT
Long Description	Heat Shrink Tubing, Flexible for High Specifications, UL/CSA Listed, Thin Wall, Shrink Ratio 2:1, 3/32 Inch/2.4mm Expanded Diameter, Transparent, 150M

Ordering

EAN	5415022276619
-----	---------------

Dimensions

Product Net Weight	2 lb 907.029 g
--------------------	-------------------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	15.4 in 391 mm
Package Level 2 Height	2.6 in 66 mm

Package Level 2 Depth /
Length

15.4 in
391 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Transparent
Flammability Hazard Rating	Flame Retardant
Number of Batteries	0
Process Temperature Rating	-67 to +212 °F -55 to +100 °C
Product Name	OTHER TUBES,PIPES AND HOSES
Product Type	Thin-Wall Heat Shrinkable Tubing
Shrink Ratio	2:1
Shrink Temperature	194 °F 90 °C
Thickness	Thin
UPC	786209891679

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	MLP93-C-E
Instructions and Manuals	MLP93-C-E

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

