

## PRODUCT-DETAILS

# OT200E03YP

## OT200E03YP BY-PASS SWITCH



### General Information

|                       |                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | OT200E03YP                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Product ID            | 1SCA123552R1001                                                                                                                                                                                                                                                                                                                                                                                                                        |
| EAN                   | 6417019543369                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Catalog Description   | OT200E03YP BY-PASS SWITCH                                                                                                                                                                                                                                                                                                                                                                                                              |
| Long Description      | Including a black plastic IP65 I-0-II pistol type handle and a handle extension for enabling smooth manual operation, shaft and bolt set for the cable connection. The handle extension is snap-on mounted on the standard handle for manual operation. The handle extension shall be removed when padlocking the standard handle. Handle padlockable in the 0-position, door interlock in the I- and II-positions and when padlocked. |

### Ordering

|                        |              |
|------------------------|--------------|
| Minimum Order Quantity | 1 piece      |
| Customs Tariff Number  | 85365080     |
| Country of Origin      | Finland (FI) |

### Popular Downloads

|                                   |                 |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 1SCC301020C0201 |
| Instructions and Manuals          | 1SCC301080M0003 |

## Dimensions

|                            |        |
|----------------------------|--------|
| Product Net Width          | 194 mm |
| Product Net Height         | 150 mm |
| Product Net Depth / Length | 236 mm |
| Product Net Weight         | 5.6 kg |

## Technical

|                                                    |                                                            |
|----------------------------------------------------|------------------------------------------------------------|
| Rated Operational Current AC-21A ( $I_e$ )         | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A    |
| Rated Operational Current AC-22A ( $I_e$ )         | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A    |
| Rated Operational Current AC-23A ( $I_e$ )         | (380 ... 415 V) 200 A<br>(500 V) 200 A<br>(690 V) 200 A    |
| Rated Operational Power AC-23A ( $P_e$ )           | (380 ... 415 V) 110 kW<br>(500 V) 132 kW<br>(690 V) 200 kW |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | q = 40 °C 200 A                                            |
| Conventional Thermal Current ( $I_{the}$ )         | Fully Enclosed 200 A                                       |
| Rated Impulse Withstand Voltage ( $U_{imp}$ )      | 12 kV                                                      |
| Rated Insulation Voltage ( $U_i$ )                 | 1000 V                                                     |
| Rated Operational Voltage                          | 1000 V                                                     |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | for 1 s 8 kiloampere rms                                   |
| Power Loss                                         | 4 W                                                        |
| Pollution Degree                                   | 3                                                          |
| Handle Color                                       | Black                                                      |
| Handle Type                                        | Handle and shaft included                                  |
| Switches Operating Mechanism                       | Mechanism at the End of the Switch<br>03 (Left Side)       |
| Distance Between Phases                            | Standard                                                   |
| Position of Line Terminals                         | Top In - Bottom Out, Bottom In - Top Out                   |
| Operating Mode                                     | Front operated                                             |
| Mounting Type                                      | Base mounting                                              |
| Number of Poles                                    | 3                                                          |
| Degree of Protection                               | Front IP20                                                 |
| Transition Type                                    | Open                                                       |

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC301194D0202 |
| Instructions and Manuals       | 1SCC301080M0003 |

## Container Information

|                       |         |
|-----------------------|---------|
| Package Level 1 Units | 1 piece |
|-----------------------|---------|

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 175 mm        |
| Package Level 1 Depth / Length | 360 mm        |
| Package Level 1 Height         | 350 mm        |
| Package Level 1 Gross Weight   | 5.6 kg        |
| Package Level 1 EAN            | 6417019543369 |

**Classifications**

|                            |                                                            |
|----------------------------|------------------------------------------------------------|
| Object Classification Code | Q                                                          |
| ETIM 5                     | EC000216 - Switch disconnecter                             |
| ETIM 6                     | EC000216 - Switch disconnecter                             |
| ETIM 7                     | EC000216 - Switch disconnecter                             |
| WEEE Category              | 5. Small Equipment (No External Dimension More Than 50 cm) |

**Categories**

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Manual bypass switches

