


PRODUCT-DETAILS

# OS125GD13N2P

## OS125GD13N2P SWITCH FUSE



### General Information

Extended Product Type	OS125GD13N2P
Product ID	1SCA123054R1001
EAN	6417019539515
Catalog Description	OS125GD13N2P SWITCH FUSE
Long Description	Switch Fuses,Front operated,4-pole,13 (Between the Poles),DIN,000,00,Handle and shaft included,Switched - With Solid Link

### Ordering

Customs Tariff Number	85365080
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC311137D0201
Instructions and Manuals	1SCC110037M0206

### Dimensions

Product Net Width	183 mm
Product Net Height	140 mm

Product Net Depth / Length	130 mm
Product Net Weight	2.6 kg 5.73 lb

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(500 V) 125 A (690 V) 125 A
Rated Operational Current AC-22A ( $I_e$ )	(500 V) 125 A (690 V) 125 A
Rated Operational Current AC-23A ( $I_e$ )	(500 V) 125 A (690 V) 125 A
Rated Operational Power AC-23A ( $P_e$ )	(220 ... 240 V) 37 kW (400 V) 55 kW (415 V) 55 kW (500 V) 75 kW (690 V) 110 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 125 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 125 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	500 V
Rated Short-time Withstand Current ( $I_{cw}$ )	for 1 s 5 kiloampere rms
Rated Conditional Short-Circuit Current ( $I_{nc}$ )	(690 V) 80 kA
Power Loss	at Rated Operating Conditions per Pole 12 W
Pollution Degree	3
Handle Type	Pistol handle and shaft included
Fourth Pole Position	Right Side
Fourth Pole Type	Switched - With Solid Link
Switches Operating Mechanism	13 (Between the Poles)
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Fuse Size	000,00
Fuse System	DIN
Operating Mode	Front Operated
Standards	IEC 60947-3
Mounting Type	Base mounting
Number of Poles	4
Terminal Type	Lug terminals
Terminal Width	20 mm
Tightening Torque	15 ... 22 N·m
Fuse Type	DIN

## Environmental

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

## Certificates and Declarations (Document Number)

CCC Certificate

CCC OS100-160G\_2015.pdf

Declaration of Conformity - CE	1SCC311137D2703
DNV GL Certificate	1SCC311125D0203
EAC Certificate	EAC OT_OTDC_OTL_OTP_OTR_OTU_OTE_OETL_OESA_OESC_OTM_OS_OSM_.pdf
Instructions and Manuals	1SCC110037M0206
RoHS Information	1SCC311137D2703

## Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	170 mm 6.7 in
Package Level 1 Depth / Length	250 mm 9.8 in
Package Level 1 Height	155 mm 6.1 in
Package Level 1 Gross Weight	2.76 kg 6.1 lb
Package Level 1 EAN	6417019539515

## Classifications

Object Classification Code	Q
ETIM 4	EC001040 - Fuse switch disconnecter
ETIM 5	EC001040 - Fuse switch disconnecter
ETIM 6	EC001040 - Fuse switch disconnecter
ETIM 7	EC001040 - Fuse switch disconnecter
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

## Categories

Low Voltage Products and Systems → Switches → Switch Fuses

