
PRODUCT-DETAILS

FCP-S5/400 230V-9h

Ind. P&S#FCP-S5/400 230V-9h



General Information

| | |
|-----------------------|---|
| Extended Product Type | FCP-S5/400 230V-9h |
| Product ID | 2CMA103374R1000 |
| EAN | 7392696033749 |
| Catalog Description | Ind. P&S#FCP-S5/400 230V-9h |
| Long Description | Panel mounted socket outlets, 3P+N+E, IP67, 400 A, 380 ... 415 V, The robust B-Line connectors are ideal for applications (tunneling, mining), where high mechanical loads may arise. Furthermore, numerous options, such as the saltwater-resistant housing, make the connectors also suitable for marine applications. Aluminum housing. Designed for high temperature. |

Ordering

| | |
|------------------------|------------------|
| EAN | 7392696033749 |
| Country of Origin | Switzerland (CH) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 275 mm |
| Product Net Height | 230 mm |

| | |
|--------------------|--------|
| Product Net Weight | 7.3 kg |
|--------------------|--------|

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 352 mm |
| Package Level 1 Depth / Length | 352 mm |
| Package Level 1 Height | 232 mm |
| Package Level 1 Gross Weight | 7.3 kg |
| Package Level 1 EAN | 7392696033749 |
| Package Level 1 Units | box 1 piece |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | NoDecNee |
| Environmental Information | 2CMC000074M0000 |

Additional Information

| | |
|----------------------------|----------------------------------|
| Additional Information | 3P+N+E |
| Ambient Temperature | -40 ... 100 °C |
| Color | Blue |
| Connection Type | Screw |
| Degree of Protection | IP67 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Outlet |
| Housing Material | Aluminium |
| Invoice Description | Ind. P&S#FCP-S5/400 230V-9h |
| Mounting Holes | 127x127 |
| Number of Poles | 5 |
| Order Multiple | 1 piece |
| Product Main Type | FCP |
| Product Name | Panel mounted socket |
| Protection Type | Splashproof |
| Rated Current (I_n) | 400 A |
| Rated Frequency (f) | 50...60 Hz |
| Rated Voltage (U_r) | 120/208 ... 144/250 V |
| Standards | IEC 60309-1, -2 |
| Sub-Function | B-line |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC700014C0016 |
| RAL Number | RAL 7001 - Silver Grey |

Classifications

| | |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

