

PRODUCT-DETAILS

CUMI-S4/400 400V-6h

Ind. P&S#CUMI-S4/400 400V-6h



General Information

Extended Product Type	CUMI-S4/400 400V-6h
Product ID	2CMA103490R1000
EAN	7392696034906
Catalog Description	Ind. P&S#CUMI-S4/400 400V-6h
Long Description	Connector Unit with Mechanical Interlock, yellow painted steel enclosure, 1200X800X375, CUMI-S4/400 400V-6h, 3P+E

Ordering

EAN	7392696034906
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	550 mm
Product Net Height	362 mm
Product Net Weight	45.6 kg

Container Information

Package Level 1 Width	883 mm
Package Level 1 Depth / Length	883 mm
Package Level 1 Height	364 mm
Package Level 1 Gross Weight	45.6 kg
Package Level 1 EAN	7392696034906
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

Additional Information

Additional Information	3P+E
Ambient Temperature	-40 ... 70 °C
Cable Diameter	20 ... 65 mm
Cable Entry Position	Up
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP55
Frequency (f)	50 Hz 60 Hz
Function	Connector Unit with Mechanical Interlock
Housing Material	Steel
Invoice Description	Ind. P&S#CUMI-S4/400 400V-6h
Mounting Holes	515x630
Number of Poles	4
Order Multiple	1 piece
Product Main Type	CUMI
Product Name	Connector Unit with Mechanical Interlock
Rated Current (I_n)	400 A
Rated Voltage (U_r)	380 ... 415 V
Standards	IEC 60309-1, -2
Sub-Function	B-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

Classifications

eClass	27440508
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

