

PRODUCT-DETAILS

363BS1

Surface inlet, 1h, 63A, IP44, 3P+E



General Information

Extended Product Type	363BS1
Product ID	2CMA167562R1000
EAN	7392696675628
Catalog Description	Surface inlet, 1h, 63A, IP44, 3P+E
Long Description	Surface Inlet, earthing sleeve position 1h, rated current 63A, IP44 splashproof, 3-poles+earth, color code Grey

Ordering

E-Number (Sweden)	2417206
E-Number (Finland)	2417206
E-Number (Norway)	2417206
EAN	7392696675628
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	107 mm
Product Net Height	117 mm
Product Net Weight	0.79 kg

Container Information

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	120 mm
Package Level 1 Height	265 mm
Package Level 1 Gross Weight	0.87 kg
Package Level 1 EAN	7392696675628
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	128.75 kg
Package Level 2 EAN	7392696073967
Package Level 2 Units	pallet (lift) 125 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660163X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1519130
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm²
Cable Entry Position	Cable entry, M32 alternative rear knock-out cable entry
Color	Grey
Connection Type	Screw
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	AC Hz
Function	Surface Inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#363BS1
Mounting Holes	170x95
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TBS
Product Name	Wall mounted inlet
Protection Type	Splashproof

Rated Current (I_n)	63 A
Rated Voltage (U_r)	Optional voltage V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Inlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000040M0001
Installation Manual	2CMC000040M0001
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440519
UNSPSC	39121406

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

