

PRODUCT-DETAILS

# 216EBS4W

## Wall mounted inlets, 2P+E, 16A, 100 ... 130 V



### General Information

Extended Product Type	216EBS4W
Product ID	2CMA101165R1000
EAN	7392696011655
Catalog Description	Wall mounted inlets, 2P+E, 16A, 100 ... 130 V
Long Description	Wall mounted inlet, 2P+E, 16A, 100 ... 130 V Clock Position Of Grounding Contact 4 hour Color code Yellow

### Ordering

E-Number (Finland)	2420139
EAN	7392696011655
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	5 piece

### Dimensions

Product Net Width	89 mm
Product Net Height	111 mm
Product Net Weight	0.20 kg

### Container Information

Package Level 1 Width	134 mm
Package Level 1 Depth / Length	177 mm
Package Level 1 Height	467 mm
Package Level 1 Gross Weight	1 kg
Package Level 1 EAN	7392696018548
Package Level 1 Units	box 5 piece

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Certificates and Declarations (Document Number)

CB Certificate	2CHC660170X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616286
REACH Declaration	2CMC700005D0001

## Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm <sup>2</sup>
Cable Diameter	25 mm
Color	Yellow
Connection Type	Screw
Degree of Protection	IP67
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216EBS4W
Mounting Holes	40x63,5
Mounting Type	Angled
Number of Poles	3
Order Multiple	5 piece
Product Main Type	EBS
Product Name	Wall mounted inlet
Protection Type	Watertight
Rated Current (I <sub>n</sub> )	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U <sub>r</sub> )	100 ... 130 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016

RAL Number

RAL 7012 - Basalt Grey

---

### Classifications

---

eClass

27440519

UNSPSC

39120000

---

### Technical

---

Wire Size

14 ... 12 AWG

Tightening Torque

WireClamp0.8 N·m

---

---

### Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

