
PRODUCT-DETAILS

332QC9

Ind. P&S#332QC9



General Information

| | |
|-----------------------|--|
| Extended Product Type | 332QC9 |
| Product ID | 2CMA102937R1000 |
| EAN | 7392696029377 |
| Catalog Description | Ind. P&S#332QC9 |
| Long Description | Industrial Connectors, earthing sleeve position 9h, 3P+E, 32A, 200 ... 250 V, Screwless terminals, color code blue |

Ordering

| | |
|------------------------|---------------|
| EAN | 7392696029377 |
| Country of Origin | Turkey (TR) |
| Minimum Order Quantity | 10 piece |

Dimensions

| | |
|--------------------|----------|
| Product Net Width | 91 mm |
| Product Net Height | 91 mm |
| Product Net Weight | 0.262 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 190 mm |
| Package Level 1 Depth / Length | 265 mm |
| Package Level 1 Height | 230 mm |
| Package Level 1 Gross Weight | 2.961 kg |
| Package Level 1 EAN | 7392696042772 |
| Package Level 1 Units | box 10 piece |

Environmental

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000072M0000 |
| RoHS Information | 2CMC700005D0001 |
| REACH Declaration | 2CMC700005D0001 |

Additional Information

| | |
|----------------------------|----------------------------------|
| Additional Information | 3P+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 2.5 ... 6 mm ² |
| Cable Diameter | 11 ... 20.5 mm |
| Cable Entry Position | Swivel |
| Color | Blue |
| Connection Type | Screwless |
| Degree of Protection | IP44 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Connector |
| Housing Material | Plastic (PA) |
| Invoice Description | Ind. P&S#332QC9 |
| Number of Poles | 4 |
| Order Multiple | 10 piece |
| Product Main Type | QC |
| Product Name | Industrial Connector |
| Protection Type | Splashproof |
| Rated Current (I_n) | 32 A |
| Rated Voltage (U_r) | 200 ... 250 V |
| Standards | IEC 60309-1, -2 |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC700014C0016 |

RAL Number

RAL 7012 - Basalt Grey

Classifications

| | |
|--------|----------|
| eClass | 27440509 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

