

---

PRODUCT-DETAILS

# MCW-S4/200 1000V-1h

## Ind. P&S#MCW-S4/200 1000V-1h




---

### General Information

Extended Product Type	MCW-S4/200 1000V-1h
Product ID	2CMA103263R1000
EAN	7392696032636
Catalog Description	Ind. P&S#MCW-S4/200 1000V-1h
Long Description	Surface mounted inlet, 3P+E, IP67, 200 A, 200 ... 250 V, The compact C-Line connectors have a robust plastic housing and are perfect for applications with limited space conditions as well as for certain industries (chemistry, food industry). Designed for high temperature.

---

### Ordering

EAN	7392696032636
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

---

### Dimensions

Product Net Width	240 mm
Product Net Height	200 mm
Product Net Weight	3.6 kg

---

**Container Information**


---

Package Level 1 Width	362 mm
Package Level 1 Depth / Length	362 mm
Package Level 1 Height	202 mm
Package Level 1 Gross Weight	3.6 kg
Package Level 1 EAN	7392696032636
Package Level 1 Units	box 1 piece

---



---

**Certificates and Declarations (Document Number)**


---

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

---



---

**Additional Information**


---

Additional Information	3P+E
Ambient Temperature	-40 ... 100 °C
Cable Diameter	45 ... 65 mm
Cable Entry Position	Anti-kink sleeve
Color	Grey
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	AC Hz
Function	Inlet
Housing Material	Plastic
Invoice Description	Ind. P&S#MCW-S4/200 1000V-1h
Mounting Holes	150x100
Number of Poles	4
Order Multiple	1 piece
Product Main Type	MCW
Product Name	Wall mounted inlet
Protection Type	Watertight
Rated Current (I <sub>n</sub> )	200 A
Rated Voltage (U <sub>r</sub> )	1000 V
Standards	IEC 60309-1, -2
Sub-Function	C-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

---



---

**Classifications**


---

eClass	27440509
--------	----------

---

## Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

