

PRODUCT-DETAILS

232QBS4C

Ind. P&S#232QBS4C



General Information

Extended Product Type	232QBS4C
Product ID	2CMA102647R1000
EAN	7392696026475
Catalog Description	Ind. P&S#232QBS4C
Long Description	Wall mounted Inlet, earthing sleeve position 4h, rated current 32A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Yellow, screwless terminals, with cover

Ordering

EAN	7392696026475
Country of Origin	Turkey (TR)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	88 mm
Product Net Height	87 mm
Product Net Weight	0.214 kg

Container Information

Package Level 1 Width	190 mm
-----------------------	--------

Package Level 1 Depth / Length	265 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	1.411 kg
Package Level 1 EAN	7392696040495
Package Level 1 Units	box 5 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm²
Color	Yellow
Connection Type	Screwless
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#232QBS4C
Mounting Holes	76x48,5
Number of Poles	3
Order Multiple	5 piece
Product Main Type	QBS
Product Name	Wall mounted inlet
Protection Type	Splashproof
Rated Current (I_n)	32 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	100 ... 130 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

