

---

PRODUCT-DETAILS

# 316RU11

Socket-outlet, panel mounting, 11h, 16A, IP44, unified flange, straight, 3P+E




---

## General Information

Extended Product Type	316RU11
Product ID	2CMA193182R1000
EAN	7392696931823
Catalog Description	Socket-outlet, panel mounting, 11h, 16A, IP44, unified flange, straight, 3P+E
Long Description	Panel mounted socket, earthing sleeve position 11h, rated current 16A, IP44 splashproof, unified flange, straight, 3-poles+earth, frequency 60 Hz, color code Red

---

## Ordering

E-Number (Sweden)	2416630
E-Number (Finland)	2416630
E-Number (Norway)	2416630
EAN	7392696931823
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

---

## Dimensions

Product Net Width	75 mm
Product Net Height	87 mm

Product Net Weight	0.21 kg
--------------------	---------

## Container Information

Package Level 1 Width	138 mm
Package Level 1 Depth / Length	158 mm
Package Level 1 Height	345 mm
Package Level 1 Gross Weight	2.1 kg
Package Level 1 EAN	7392696661829
Package Level 1 Units	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1406 kg
Package Level 2 EAN	7392696079488
Package Level 2 Units	pallet (lift) 660 piece

## Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

## Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm <sup>2</sup>
Cable Diameter	13 ... 17 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316RU11
Mounting Holes	60-61x60-61

Mounting Type	Unified straight flange
Number of Poles	4
Order Multiple	10 piece
Product Main Type	ERU
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current ( $I_n$ )	16 A
Rated Frequency (f)	60...60 Hz
Rated Voltage ( $U_r$ )	440 ... 460 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7001 - Silver Grey

---

## Classifications

eClass	27440504
UNSPSC	39121406

---

## Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

---

## Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

